

# Terrazzo Pescatori

## Terrazzo Italiano

### Technical Data Sheet

|                          |                                                                                                                                                                                                                                                                                                             |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| TYPE                     | Cement Marble                                                                                                                                                                                                                                                                                               |
| MATERIAL CHARACTERISTICS | Cement marble is produced by blending marble chips – selected for colour and grain size – with cement. Compared with resin marble it offers greater solidity and strength, a tactile, textured feel and a lower price thanks to the cement base, which is more economical than the use of specialty resins. |
| SLAB DIMENSIONS          | 305 x 124 x 80 cm                                                                                                                                                                                                                                                                                           |
| POSSIBLE RESTRICTIONS    | To preserve the material correctly, avoid pouring acidic substances on it, as these could damage the surface. For cleaning, use mild products free from solvents or corrosive substances.                                                                                                                   |
| AVAILABLE FINISHES       | Sandblasted, brushed, honed, polished                                                                                                                                                                                                                                                                       |

### Physical & Mechanical Properties

|                                  |                                   |
|----------------------------------|-----------------------------------|
| APPARENT DENSITY                 | 2.40 – 2.60 kg/dm <sup>3</sup>    |
| FLEXURAL STRENGTH                | 11.5 – 24.6 MPa                   |
| COMPRESSIVE STRENGTH             | 90 – 120 MPa                      |
| ABRASION RESISTANCE              | 34.5 – 36 mm                      |
| COEFFICIENT OF THERMAL EXPANSION | 14 – 24 × 10 <sup>-6</sup> m/m·°C |
| IMBIBITION COEFFICIENT           | < 0.2 % (by volume)               |

The technical data, supplied by the quarries, may contain inaccuracies or be incomplete and must therefore be regarded as purely indicative. TERZI SERVICE SRL accepts no liability in this respect.

Terzi Service Srl - Via Selva, 41 - 24060 - Zandobbio (BG) - Italy - tel. +39 035 94 01 23 - info@terziservice.com - www.terziservice.it